

Brighten Every Moment

Solid Plus Series

Indoor



HOB



High Protection



LED Lamp Repair Machine

Superior Cabinet

- **Super Slim – 29.5mm**


Combining elegance and robustness

- **Ultra Light – 17.3 kg/m²**

Facilitating effortless installation

- **Exceptionally Robust**

Tensile strength of up to 2,000N
Splicing of 50 rows / 17 m, no deformation



Convenient Splicing & Installation

- **Big Board – 600*337.5 mm, 16:9**

More accurate and easier splicing, compatible with diverse resolutions

- **Flexible Wiring**

Cascading both horizontally and vertically, saving wiring costs

- **Removable Back Frame Plate**

With cables passing through, preventing tangled cords at the screen bottom

Unique Advantages



Higher Protection Level

- Enhanced protection with glue, resistant against water, moisture, corrosion, dust, static, and oxidation



Better Visual Performance

- A matte screen to alleviate eye strain
- Increased contrast ratio and display consistency




Lamp Repair Machine

- A self-developed LED lamp repair machine to improve HOB lamp board repairs and address dead LED issues

Application Scenarios



Command Center



Auditorium & Lecture Hall



Meeting Room



Retail Store & Cinema



Studio

Key Spec

	DS-D4012CW-2FQ	DS-D4015CW-2FQ	DS-D4018CW-2FQ
Pixel Structure		HOB	
Pixel Pitch (mm)	1.25	1.56	1.8
Cabinet Dimension (W × H × D, mm)		600 × 337.5 × 29.5 (23.622" × 13.287" × 1.161")	
Cabinet Resolution (W × H)	480 × 270	384 × 216	240 × 136
Cabinet Weight		3.4 Kg(7.496 lb)	
Cabinet Material		Aluminium die casting	
Protection Level		IP65 (Module)	
Brightness (nits)		600	
Viewing Angle		160°(H)/160°(V)	
Contrast Ratio		5000:1	
Peak Consumption (W/m ²)	≤ 460	≤ 390	≤ 400
Refresh Rate (Hz)		3840	
Grey Level (bit)		16	



Hikvision

HikvisionHQ

HikvisionHQ

Hikvision Corporate Channel

hikvisionoverseas

Hikvision Commercial Display

HikvisionOverseas

HIKVISION