



## Flexible Solutions

Choose any combination of our identification sensors and build your own speed gate solution.

#### **Fingerprint Reader:**

- Stores up to 5,000 fingerprints
- Instant verification within 1 second

#### Facial Recognition Terminal:

- Stores up to 50,000 faces
- Instant verification within 0.2 seconds
- 0.3-3 meter recognition distance
- Recognition even against harsh backlight
- Distinguishes live human faces from pictures and videos

# Advanced Features

Unlock more advanced features with the Hik-Central Professional management platform, such as alarm linkage, anti-passback, and much more.

#### Customizable swing gate direction and operating modes:

- Always Open: Allowing access to all
- Always Closed: Limited access
- · Verification: Access by verification only
- Adjustable open interval fits various throughputs
- Gates unlocks automatically if power is interrupted
- Works on and offline with remote management via software
- · Prevents unauthorized break-ins and tailgating
- Remote control the speed gate by keyfob
- Customized audio promotion for authentication



# **Impeccable Quality**

Designed and manufactured in-house by Hikvision, these swing gates offer the best-in-class quality and the highest efficiency.

## Faturing:

- Stainless steel meets the SUS304 standard
- Anti-crash protection with 1.2 2.0 mm Stainless Steel
- Guaranteed 6 million MCBF (Mean Countdown Between Failures)
- 12 24 pairs of IR detectors
- High throughput at 20 60 persons per minute (\*Actual throughput is affected by person pass rate and pass method.)
- Anti-crash swing, flap, and tripod panel
- Flexible options with customizable width and number of passages
- Immediate response (less than 0.5 seconds)





# MinMoe Facial Recognition Terminal

Combined with the Speed Gate through RS485, Wiegand, or I/O signal the Hikvision Facial Recognition Terminal DS-K5671-Z provides an intelligent facial recognition access control solution,

### Faturing:

- Storage of up to 50,000 faces
- HD face picture with 2 MP camera
- Up to 99% recognition rate with excellent performance underbacklight, dim light, and strong light environments
- Fast, remote facial registration
- Anti-spoofing detection support, distinguishing live faces from pictures and videos
- 0.3 3 meter recognition distance

# **Product Family**

## Swing Speed Gate —



## DS-K3B501S/DS-K3B501SX

- MCBF: 6 million times
- IR Sensor: 12 pairs
- Throughput: Up to 60 persons per minute
- Built-in controller and reader
- Thickness: 1.2 mm SUS304



#### DS-K3B601/DS-K3B601SX

- MCBF: 6 million times
- IR Sensor: 12 pairs
- Throughput: Up to 60 persons per minute
- Built-in controller and reader
- Thickness: 1.5 mm SUS304



#### DS-K3B411/DS-K3B411X

- MCBF: 3 million times
- IR Sensor: 6 pairs
- Throughput: Up to 60 persons per minute
- Bulit-in controller and reader
- Thickness: 1.2 mm SUS304



## DS-K3B801/DS-K3B801SX

- MCBF: 6 million times
- IR Sensor: 24 pairs
- Throughput: Up to 60 persons per minute
- Built-in controller and reader
- Thickness: 2.0 mm SUS304

## Tripod Turnstile \_\_\_\_\_



#### DS-K3G501

- MCBF: 3 million times
- Throughput: More than 35 persons per minute
- Built-in controller and reader
- Thickness: 1.5 mm SUS304



## DS-K3G411

- MCBF: 3 million times
- Throughput: More than 35 persons per minute
- Bulit-in controller and reader
- Thickness: 1.2 mm SUS304

## Value Flap Speed Gate \_\_\_\_\_



#### DS-K3Y501/DS-K3Y501SX

- MCBF: 6 million times
- IR Sensor: 12 pairs
- Throughput: Up to 60 persons per minute
- · Built-in controller and reader
- Thickness: 1.5 mm SUS304

# **Application Scenarios**

## Swing Speed Gates \_\_\_\_\_

- Quick access
- Flexible product options
- Adjustable lane width for various scenarios









Office Scenario

**Education Institution** 



Hotel



Residence Community

## Tripod Turnstiles \_\_\_\_\_



Factory





• Better performance for anti-tailgating

- Flexible product options
- Fixed lane width for appropriate scenarios



## Flap Speed Gates \_

- Enhanced accessing speeds
- High verification accuracy
- Regular lane width










Train Station

Scenic Area

## **Turnstile Solution Showcase**







# **Dedicated Face Modules** for Turnstile Solutions

## 01. Easy to Integrate with Turnstiles

- Standard Wiegand output
- I/O signal output

## **02. Enhanced Verification Speeds**

Faster verification based on deep learning algorithm (1:N < 0.2 seconds)

## 03. Zero-light Recognition

Fast recognition speed in non-light environments (1:N < 0.2 seconds)

## 04. Simple Registration

Register via device or imported image library

## **05. Anti-spoofing Detection**

Access denied when using pictures, video, or other media as counterfeit verification

## 06. Industrial Design

- 7" Touchscreen
- IP65 Water protection (excludes DS-K5671-ZH)

## **07. Abundant Applications**

- Video intercom integration
- Network video recorder (NVR) integration

DS-K5671-ZH	
DS-K5671-ZU	
DS-K5671-ZV	
Device Capacity	
50,000 Faces	100,000 Event Records