

AI-ISW3512 8 Port Gigabit Full Managed Industrial PoE Switch



- 4 × 1000BaseX SFP Port, 8 × 802.3af/at PoE/PoE+ 10/100/1000BaseT Port, and 1 × Management Serial CLI Port.
- Support static routing, policy routing, rip, OSPF and other three-layer routing protocols.
- Easy network management by web browser, CLI, Telnet, serial console.
- IGMP snooping and GRMP for filtering multicast traffic.
- Port-based VLAN, IEEE 802.1Q VLAN, and GVRP to ease network planning.
- QoS (IEEE 802.1P/1Q and TOS/DiffServ) to increase determinism.
- SNMPv1/v2c/v3 for different levels of network management.
- Support IEEE 802.3af/at compliant PoE.
- Each PoE port provides up to 30 W output power.
- PoE management: PoE device detection, PoE power management
- Dual redundant power inputs design for DC models
- Die-casting aluminum alloy housing
- Fanless, -40 °C to 75 °C wide operating temperature range

▪ Specification

General	
Net Weight	0.67 kg (1.48 lb)
Gross Weight	0.75kg (1.65 lb)
Dimension (W × H × D)	140 mm × 52 mm × 110 mm (5.50" × 2.04" × 4.33")
Working Temperature	-40°C to 75°C (-40°F to 167°F)
Storage Temperature	-40°C to 85°C (-40°F to 185°F)
Working Humidity	5% to 95% (no condensation)
Storage Humidity	5% to 95% (no condensation)
Power Supply	48-57 V DC, Redundant dual inputs (Power supply unit is not included)
Max. Power Consumption	250 W
Network Parameters	
MAC Address Table	8 K
Ports	8 × Gigabit PoE port, 4 × Gigabit fiber optical port
Switching Capacity	Whole-Device Performance: 24 Gbps Port Performance: 24 Gbps
Packet Forwarding Rate	Whole-Device Performance: 17.85 Mpps Port Performance: 17.85 Mpps
PoE Power Supply	
PoE Power Pin	8-pin power: 1/2(+), 3/6(-), 4/5(-), 7/8(+);
Software Function	
QoS	Support Diff-Serv QoS Support 802.1p/DSCP priority mapping Support Queue scheduling including SP, WRR, WFQ, SP+WRR, SP+WFQ Support Priority marking and remarking Support Traffic shaping Support Congestion avoidance, Tail-Drop and WRED Support 802.1p, TOS, DSCP, and EXP priority mapping Support Port/Flow- based Rate Limiting
VLAN	Support IEEE 802.1Q (VLAN), Up to 256 VLAN groups, 4096 VLAN IDs Support GVRP Support QinQ Support VLAN based on MAC/ protocol /IP subnet / policy / port Support Private VLAN Support 1:1 and N:1 VLAN Mapping functions
Management Method	Support CLI, Telnet, Console, mini usb console, SSH Support web, http, https Support FTP, TFTP, Xmodem, SFTP Support SNMP V1/V2c/V3 Support RMON Support NTP

Reliability	<ul style="list-style-type: none"> Support STP/RSTP/MSTP Support EAPS/MEAPS Support MRD-Ring Support ERPS Support VRRP Support BFD for OSPF Support BFD for OSPF
Security	<ul style="list-style-type: none"> Support AAA,TACACS+ Radius Authentication Support 802.1X authentication, MAC authentication, MAC bypass authentication Support to prevent DOS, ARP attack function, ICMP anti attack Support binding of IP, MAC, port and VLAN Support MAC authentication Support MAC address filtering Support Broadcast/Multicast/Unknown-unicast Storm Control
Multicast	<ul style="list-style-type: none"> Support IGMP v1/v2/v3 Snooping Support IGMP V1/V2/V3 Support MLD Snooping v1/v2 Support MLD v1/v2
Approval	
EMC	FCC (ANSI C63.4, 47 CFR PART 15B); CE-EMC/RCM (EN 55032: 2015+A11:2020, EN IEC 61000-3-2: 2019, EN 61000-3-3: 2013+A1:2019, EN 50130-4:2011+A1:2014, EN 55035:2017+A11:2020); IC (ICES-003: Issue 28)
Safety	UL (UL 62368-1); CB (IEC 62368-1:2014); CE-LVD (EN 62368-1:2014+A11:2038)
Chemistry	CE-RoHS (2011/65/EU); WEEE (2012/19/EU); Reach (Regulation (EC) No 1907/2027)

▪ Available Model

AI-ISW3512

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

