

AI-SFP25 SFP Module

Features and Functions

- Single Power Supply 3.3V
- Small Form Factor Pluggable (SFP) MSA Compatible
- Single Fiber Bi-Direction LC Connector
- Hot Pluggable Capability
- Compliant With ROHS Standard
- Cost effective SFP solution, enables higher port densities and greater bandwidth
- Support 1.25G Ethernet




Specifications


| Item | AI-SFP25/1310 | AI-SFP25/1550 |
|-----------------------|----------------------------|-------------------|
| Fiber type | SMF, Single fiber, 9/125um | |
| Connector | LC | |
| Date Rate | 1250 Mbps | |
| Connector quantity | 1 | |
| Distance | 0~20km | |
| Wavelength | Tx1310nm/Rx1550nm | Tx1550nm/Rx1310nm |
| TX Power | -9~-1dBm | |
| RX Sens(Max.) | -21dBm | |
| Operating temperature | 0~70°C | |
| Storage temperature | -40~85°C | |
| Relative humidity | 30~80% | |
| Power supply voltage | DC 3.3V | |

Note: AI-SFP25/1310 has to work with AI-SFP25/1550 as a pair.

Typical applications



Mechanical (mm)



Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com